



Tubo di lancio girevole 270°  
270° rotary ejection pipe  
Goulotte d'évacuation orientable 270°  
Tubo de descarga giratorio  
270° drehbares Auswurfrohr  
Uitwerpijp 270° draaibaar  
Труба выброса вращающаяся на 270°



Profondità di gettata regolabile  
Adjustable throw depth  
Déflecteur réglable  
Profundidad de expulsión regulable  
Einstellung der Schussweite  
Verstelbare uitwerphoogte  
Регулируемая глубина метания



Timone regolabile in altezza, per versione Diesel  
Drawbar with adjustable height, for Diesel version  
Timon réglable en hauteur, pour la version Diesel  
Timón regulable en altura, de la versión Diesel  
Höhenverstellbare Deichsel, für Diesel-Version  
Regelbare dissel in hoogte, voor Diesel versie  
Регулируемое по высоте дышло, для дизельной версии



Motore diesel montato su antivibranti  
Diesel engine mounted on silent blocks  
Moteur diesel monté sur anti vibrants  
Motor diesel montado sobre antivibrantes  
Dieselmotor auf Schwingungsdämpfer montiert  
Op antivib gemonteerde dieselmotor  
Дизельный двигатель, установленный на виброизоляционное устройство



Ganci di sollevamento  
Lifting hooks  
Crochets de levage  
Ganchos de levantamiento  
Aufhanghaken  
Haken voor het optillen  
Крюки для поднятия



Utensili di taglio qualitativamente testati con marchio originale  
Quality tested cutting tools with original trademark  
Outils de coupe testés qualitativement avec marque de fabrique  
Herramienta de corte con marca de fábrica original y calidad probada  
Getestete Qualitäts-Schneidwerkzeuge mit originale Markenzeichen  
Op kwaliteit geteste gereedschappen met het originele merk  
Качественные протестированные инструменты резки с оригинальной торговой маркой

### CARATTERISTICHE TECNICHE / TECHNICAL CHARACTERISTICS

MODELLO MODEL	R280BH21 OTRGN R280BH21 OTRON R280BH21 OTROFRAN	-M	R280DK26 OTRGN R280DK26 OTRON R280DK26 OTROFRAN	-M	R280DL26 OTRGN R280DL26 OTRON R280DL26 OTROFRAN	-M	R280BH21 CN	-M	R280DK26 CN R280DL26 CN	-M	R280TN	-M
MOTORE ENGINE	HONDA GX630		KUBOTA D1105		LOMBARDINI LDW1003		HONDA GX630		KUBOTA D1105 LOMBARDINI LDW1003		TRATTORE TRACTOR	
POTENZA POWER	hp 21 (kW 15,5)		hp 26,5 (kW 19,5)		hp 26,5 (kW 19,5)		hp 21 (kW 15,5)		hp 26,5 (kW 19,5)		MIN hp 35 (kW 26)	
Ø TRITTURABILE Ø TO SHRED	* 150 mm		* 150 mm		* 150 mm		* 150 mm		* 150 mm		* 150 mm	
LUNGHEZZA LENGTH	3795 mm		3795 mm		3795 mm		2850 mm		2850 mm		3590 mm	
LARGHEZZA WIDTH	1450 mm		1450 mm		1450 mm		1500 mm		1500 mm		1540 mm	
ALTEZZA HEIGHT	2280 mm		2280 mm		2280 mm		2280 mm		2280 mm		2390 mm	
ALTEZZA DI INTRODUZIONE INTRODUCTION HEIGHT	700 mm		700 mm		700 mm		800 mm		800 mm		810 mm	
ALTEZZA DI SCARICO DISCHARGE HEIGHT	2280 mm		2280 mm		2280 mm		2380 mm		2380 mm		2390 mm	
APERTURA PER INTRODUZIONE INTRODUCTION OPENING	1205x855 mm		1205x855 mm		1205x855 mm		1205x855 mm		1205x855 mm		1205x855 mm	
APERTURA DI TRITURAZIONE SHREDDING OPENING	270x490 mm		270x490 mm		270x490 mm		270x490 mm		270x490 mm		270x490 mm	
N° MARTELLI HAMMERS No.	24	24	24	24	24	24	24	24	24	24	24	24
N° LAME / BLADES No.	2	—	2	—	2	—	2	—	2	—	2	—
PESO / WEIGHT Kg	680 Kg		750 Kg		750 Kg		1130 Kg		1200 Kg		630 Kg	
PRODUZIONE ORARIA HOURLY PRODUCTION	* 13-18 m³/h		* 13-18 m³/h		* 13-18 m³/h		* 13-18 m³/h		* 13-18 m³/h		* 13-18 m³/h	

- M Rotore di triturazione a martelli mobili reversibili / Shredding rotor with mobile reversible hammers / Rotor de broyage avec marteaux mobiles reversibles / Rotor de trituración con martillos móviles reversibles / Rotor für die Zerkleinerung mit beweglichen und umkehrbaren Messern / Hakselrotor met omkeerbare beweeglijke hamers / Измельчающий ротор с подвижными реверсивными молотками.

\* Dato dipendente dal tipo di materiale e dalle condizioni di lavoro. / It depends on the kind of material and on the working conditions. / Ces données peuvent changer selon le type de matériel et les conditions de travail. / Estos datos pueden cambiar según el tipo de material y las condiciones de trabajo. / Daten, die von der Art des Materials und den Arbeitsbedingungen abhängen. / Deze gegevens zijn afhankelijk van het soort materiaal en de werkomstandigheden. / Это зависит от вида материала и от условий труда.

La Ditta NEGRI in qualunque momento si riserva il diritto di apportare alla propria produzione modifiche e miglioramenti ritenuti necessari a suo insindacabile giudizio. / At any time and at its incontestable discretion, NEGRI reserves the right to modify and improve its products, if considered necessary. / Dans n'importe quel moment et à son jugement sans appel, la maison NEGRI se garde le droit d'apporter des modifications et des améliorations à ses produits, si considérées nécessaires. / En cualquier momento y a su incuestionable juicio, la empresa NEGRI tiene el derecho de aportar a su producción modificaciones y mejoras consideradas necesarias. / Op elk gewenst moment en naar haar onbetwistbare discretie, NEGRI behoudt zich het recht voor om te wijzigen en verbeteren van haar producten, indien nodig geacht. / В любое время и на своем неоспоримом усмотрении NEGRI оставляет за собой право изменять и совершенствовать свою продукцию, если это будет сочтено необходимым.



46010 CAMPITELLO di MARCAMA (MN) ITALY • Via Motella, 33  
Phone 0039 0376 926162 • Fax 0039 0376 925329  
http://www.negri-bio.com • E-mail: info@negri-bio.com

**BIOTRITURATORE  
BIO-SHREDDER  
BIO-BROYEUR  
BIO-TRITURADOR  
BIO-HÄCKSLER  
BIO-HAKSELAAR  
БИОИЗМЕЛЬЧИТЕЛЬ**

**R280**  
**NEGRI**  
*garden equipment*

Diesel  
Lombardini LDW1003  
hp 26,5 (kW19,5)  
omologato traino  
patente B  
velocità max. 80 Km/h  
with 80 km/h  
(maximum speed)  
homologated trailer  
for road transport  
with driving licence type B



Versione a trattore  
Tractor version



